

OPSIS LiquidLINE HydROC

Reduce cost and errors for
Total Fat determinations



THE HYDROC HYDROLYSIS UNIT

OP SIS LiquidLINE brings an innovative solution for Acid Hydrolysis, making Total Fat determinations more efficient and safe. The hazardous Hydrolysis process can now safely be performed with up to six samples simultaneously. The unique HydROC filter brings additional cost and time savings.

SAVE COSTS WITH CLEVER FILTER TECHNOLOGY

- The HydROC filter can be used several times* which makes it more cost efficient than any other solution on the market.
- Clever solution saves cost on other consumables such as Celite** , Quartz sand and hydrolysis filters.
- System compatible with several other extraction systems on the market.

REDUCE ERRORS IN TOTAL FAT ANALYSIS

- The HydROC filter can be used in both hydrolysis and extraction steps, avoiding sample transfer errors and saving time.
- The HydROC and SoxROC batch handling system saves time when moving samples between hydrolysis and extraction.
- Complete separation of samples removes the risk for contamination.

RELIABLE DESIGN

- The Acid Hydrolysis is performed in a closed system, reducing risks for the operator.
- The OP SIS LiquidLINE BlackLINE coating provides unique corrosion protection.
- Complies with standardised methods.

* Amount of times each filter can be used varies with application

** Not needed for standard applications

AS EASY AS 1-2-3

The HydROC is easy to manage with only three steps. Risk for operator introduced errors can be minimised.

- Insert up to six samples inside the HydROC unit. Use same filter holder as for the OPSIS LiquidLINE SoxROC extraction unit. Separation of each sample removes any risk for contamination.
- Run the Acid Hydrolysis, adjust the temperature as the hydrolysis progresses. Remove the acid by opening the drain valves and rinse with water. The operation is safe with no contact with Acid.
- Place condensers in cooling position and move samples to the SoxROC cup stand.



Easy to insert your sample



Oven glass makes it easy to follow the hydrolysis

THE HYDROC FILTER

The unique HydROC filter offers flexibility and cost savings for your total fat determinations.

- The HydROC filter can be used several times*.
- One single filter for both hydrolysis and extraction removes the need for separate hydrolysis filters and cellulose thimbles, which saves cost. A single filter also reduces time and complexity when moving samples, which leads to less errors.
- The HydROC filter can also be used together with other systems.



Separate Cooling position for your condensers

UPGRADE WITH CRUDE FIBER

The HydROC unit can be upgraded with the Fiber Expansion kit - allowing Crude Fiber analysis on the same instrument.

Acid
Hydrolysis Filter(s)
Celite
Quartz sand
Cellulose thimble
HydROC Filter
Extraction Solvents

Save costs for Total Fat Analyses



OPSIS AB, Box 244
SE-244 02 Furulund Sweden
Telephone +46 46 72 25 00
Telefax +46 46 72 25 01
E-mail info@opsis.se
www.liquidline.se

Specifications subject to change without notice



LP1021
2021 02

OPSIS[®]
LIQUIDLINE[®]

OPSIS AB • +46 46 72 25 00 • info@opsis.se • www.liquidline.se